

- DP-32A (3 1/2 Digital Panel Meter, AC Voltage/Current Meter)
- DP-32C (3 1/2 Digital Panel Meter, RTD Temperature Meter)
- DP-32D (3 1/2 Digital Panel Meter, DC Voltage/Current Meter)
- DP-32T (3 1/2 Digital Panel Meter, True RMS Voltage/Current Meter)
- DP-42A (4 1/2 Digital Panel Meter, AC V or A Meter)
- DP-42D (4 1/2 Digital Panel Meter, DC V or A Meter)



MODEL	DP-42D	DP-42A	DP-42T
Display	4 1/2 digits (19999), 0.56" LED high		
Conversion Rate	2.5/Sec. (DC) or 1/Sec. (AC)		
Span Adjustment	±10%		
Polarity Display	"—" symbol is displayed automatically		
Over range Indication	"0000" flash		
Accuracy	DC±0.05%FS.±1digit AC±0.1%FS.±1digit RTD±0.2%FS.±1digit		
Operating Temp	0~60°C/ Below 80%R.H.		
Storage Temp	-10~70°C/ Below 70% R.H.		
Power Supply	AC 115/230V±10%, 50/60Hz		
Option	DC 12, 24, 48, 120V±20%,		
Power Consumption	Approx.2VA		
Weight	Approx. 320g(DP-42),450g(DPA-42)		
Dielectric Strength	AC 1500V/1min (Input/Power)		
Isolation Resistance	More than 100MΩ at 500VDC		
Dimensions	96(W) x 48(H) x 144(D)mm----DPA-42 96(W) x 48(H) x 104(D)mm----DP-42		
Panel Cut-Out	91.5(W) x 44(H)mm		
Features	Measuring DC V/A, AC V/A		
	Measuring RTD Temp		
	4~20mA , 1~5V measurement		
	Isolated analog output		

MODEL	DP-32D	DP-32A	DP-32T	DP-32C
Display	3 1/2 digits (1999), 0.56" LED high			
Conversion Rate	2.5/Sec. (DC) or 1/Sec. (AC)			
Span Adjustment	±10%			
Polarity Display	"—" symbol is displayed automatically			
Over range Indication	"1" or "-1"			
Accuracy	DC±0.1%FS.±1digit AC±0.25%FS.±1digit RTD±0.2%FS.±1digit			
Operating Temp	0~60°C/ Below 80%R.H.			
Storage Temp	-10~70°C/ Below 70% R.H.			
Power Supply	AC 115/230V±10%, 50/60Hz			
Option	DC 12, 24, 48, 120V±20%,			
Power Consumption	Approx.2VA			
Weight	Approx. 320g(DP-32),250g(DP-732)			
Dielectric Strength	AC 1500V/1min (Input/Power)			
Isolation Resistance	More than 100MΩ at 500VDC			
Dimensions	96(W) x 48(H) x 104(D)mm----DP-32 72(W) x 36(H) x 117(D)mm----DP-732			
Panel Cut-Out	91.5(W) x 44(H)mm----DP-32 68(W) x 33(H)mm----DP-732			